

833 LOW CUT LACE ESD SAFETY SHOES

SIZE: UK 4 - 12



MATERIAL DESCRIPTION

UPPER	COW FULL GRAIN - THICKNESS: 1.8 - 2.0 MM
COLLAR & TONGUE	HIGH ABRASION ECO LEATHER
LINING	BEIGE AIRMESH LINING 300GSM
VAMP LINING	NON-WOVEN FABRIC LINING
THREAD	ANTIWICK BONDED NYLON
EYELET	NYLON PLASTIC EYELET
INSOLE	2.0mm ANTISTATIC INSOLE
COUNTER	THERMOPLASTIC 1.1 – 1.3mm
FOOTBED	FULL PADDED
OUTSOLE	DUAL DENSITY DIRECT INJECTION POLYURETHANE + NON MARKING NITRILE RUBBER (NBR)
TOE CAP	STEEL TOE CAP COMPLY TO EN22568-1
NAIL PENETRATION	ANTI PERFORATION FABRIC MID-SOLE EN 12568 NAIL PENETRATION RESISTANT 1100N
SHOE LACE	POLYESTER SHOE LACE
PACKING	CORRUFATED PRINTED BOX

ADDITIONAL FEATURE!

ESD	EXCELLENT DISCHARGE CAPABILITY, THE SHOE IS SUITABLE FOR WORK IN ESD SENSITIVE OR ELECTROSTATICALLY PROTECT AREA (EPA) 
-----	---